

## Express yourself, express upgrade.

We are all aware of the fact that the speakers' quality is crucial for the quality of an audio system.

If your home system doesn't satisfy you, it is enough to replace your speakers with our new Express to perceive immediately an enormous improvement with a higher sound level and more definition.

Express has been worked to the smallest detail in order to access to the "French Sound" without any other modification.

"French Sound" is a subtle and very specific balance designed to accurately reproduce the music's midrange details whilst preserving all the emotions of the voice. It faithfully reproduces the original dynamics of the original recording but diligently retains all the nuances and vocal clarity that makes the music come alive.

Express is the compromise for those whose priorities are both the quality and the price.

Guy BONNEVILLE, fondateur de BLAM BLAM founder





## EXPRESSS.

**165ES** 



This kit is composed of two woofers, two tweeters and two separated high pass 6dB/octave crossovers

165 mm (6.5") « French Sound » high-sensitivity 2-way component speaker Max power 120 W - Nominal power 60 W Frequency response 65 Hz - 25 kHz Sensitivity 93.5 dB - Impedance 2  $\Omega$ 

• Woofer:

Specific basket in stamped steel

Treated and tropicalized cellulose pulp cone

Butyl rubber surround

Long life «Conex» damper

25 mm (1") voice coil with kapton former

80 mm x 15 mm (3.1" x 0.6") motor assembly (Y30)

Thick magnetic circuit (5 mm)

- 20 mm (3/4") high quality soft dome tweeter N38 neodymium motor
- 6 dB/octave high-pass separated crossover

165**EC** 



This kit is composed of two woofers with two coaxial tweeters and two integrated high pass 6dB/octave crossovers

165 mm (6.5") «French Sound» high-sensitivity coaxial speaker system

Max power 120 W - Nominal power 60 W

Frequency response 65 Hz - 25 kHz Sensitivity 93.5 dB - Impedance 2  $\Omega$ 

• Woofer:

Treated and tropicalized cellulose pulp cone
Butyl rubber surround
Long life «Conex» damper
25 mm (1") voice coil with kapton former
80 mm x 15 mm (3.1" x 0.6") motor assembly (Y30)
Thick magnetic circuit (5 mm)

- 20 mm (3/4") high quality soft dome coaxial tweeter N38 neodymium motor
- 6 dB/octave high-pass integrated crossover

Specific basket in stamped steel





